



P.K.G. Exports Pvt. Ltd.



PRODUCT CODE : : PKG/R0/18

MILD STEEL PIPES (PLAIN END/SCREWED SOCKETED)

SPECIFICATION :: IS 1161, ID 3589, ISS 1239, BS 1387, BS 1775, BS 1139 PART 1, ASTM A120 SCH 40, ASTM A53, SCH 40, API 5 L GR A&B, API 5L X 42, 5L X 46 DIN 2439, 2440 & 2441, JISG 3452, ISO 65, ISO 559

WELDING TECHNOLOGY :: HIGH FREQUENCY ELECTRIC RESISTANCE WELDING AND ALSO CONTINUOUS WELDING

NOMINAL BORE (MM) :: 15, 20, 25, 32, 40, 50, 65, 80, 100, 125, 150, 175, 200.

CLASS :: A 1 TYPE, LIGHT, MEDIUM & HEAVY

O.D (MM) :: 219.1, 273.05, 323.8, 355.6, 406.4 (LARGER DIA PIPES)

WALL THICKNESS :: FROM 1.5 TO 14 (MM)

LENGTH (METER) :: 6, 9, 12 AND AS PER CUSTOMERS REQUIREMENT

TOLERANCE :: ON LENGTH AND OUTSIDE / INSIDE DIAMETER WILL BE AS PER THE STIPULATED PIPE SPECIFICATION.

COATING :: WITH OR WITHOUT VARNISH COATING (CUSTOMER'S OPTION)

INVOICE :: AS PER MUTUAL AGREEMENT FOR THEORITICAL
OR ACTUAL WEIGH

END PROTECTORS :: PVC END PROTECTORS FOR P/E PIPES AND
STEEL SOCKETS FOR SOCKETED PIPES.

PACKING :: IN BUNDLES BETWEEN 1 TO 3 MT WITH UNIFORM
PIECE COUNT PER BUNDLE, 4 TO 5 SIGNODE
BANDS STRAPPED AND FASTENED AT EQUIDISTANT
PLACES.

ADDITIONAL INFORMATION : :