



P.K.G. Exports Pvt. Ltd.



PRODUCT CODE : : PKG/R0/21

SAW PIPES (SUBMERGED ARC WELDED STEEL PIPES)

SPECIFICATION : : API 5L GR A & B, API 5L X 42, 46, 52, 56, 60, 65, 70, & 80 ASTM A252 GR 1,2,& 3, DIN 17172 GR 290, 7 TM TO 480, 7 TM & B.S.T. 3601 - 3602, BS 1775/ 64 API 2B.IS 3589,1978 / 82 YST 210 & YST 240.

MAIN APPLICATION : : PETROLEUM AND FERTILIZER INDUSTRIES, SOUR OIL AND GAS FIELDS, PRESSURE VESSELS AND WATER/ SWAGE PROJECTS.OFFSHORE AND ONSHORE INSTALLATIONS.

OUTSIDE DIAMETER : : MINIMUM 406.4 M (16 INCH) MAX 1219 MM (48 INCH)

WALL THICKNESS : : MIN : 6 MM MAX : 32 MM

LENGTH : :12 METER (40 FEET) WITH PROVISION UPTO 24 METERS (80 FEET)

INVOICE : : THEORITICAL WEIGHT

END : : PLAIN ENDS

TESTING : : TESTING ARRANGEMENTS FOR BOTH DESTRUCTIVE AND

NON DESTRUCTIVE TEST CONFROMING TO AMERICAN
PETROLEUM INSTITUTE STANDARDS.

COATING : : PROTECTIVE COATING IS APPLIED ON THE PIPES BEFORE
SHIPMENT.

INSTALLED CAPACITY : : PROTECTIVE COATING IS APPLIED ON THE PIPES
BEFOR SHIPMENT

ADDITIONAL INFORMATION :